

## OUR SYMBOLS



Digital print



Lightness



Easy transport



Fireproof material



Breathable fabric



UV protection



Fireproof material  
available



Water repellent material



Insulating material



Machine washable



Recycled



Certified



**elleerre®**  
Dove c'è passione

**Easy-Gazebo**

◆ Easy-Gazebo LIGHT

◆ Easy-Gazebo PRO





Easy-Gazebo PRO has an aluminium structure, while the roof and sidewalls are digital printed and fully customizable. The Class 1-certified fabric is waterproof and fireproof, making all ElleErre gazebos suitable also for indoor use.

The roof, the pelmets and the sidewalls are available in a range of neutral colours, without customization (Mod. STANDARD), while the version Roof Easy-Gazebo can be fully customized with no limits for colours or graphics. It is also possible to print high definition pictures on the sidewalls and the roof, with no additional costs.

In the measures 3x3 m e 3x4,5 m, the frame Easy-Gazebo Light is also available with hexagonal aluminium structure poles, which are lighter and cheaper. Both the PRO and LIGHT structures can be folded and opened in a few seconds, allowing a quick installation.

These gazebos are delivered with rods, anchoring pegs and wheeled carry-on case for an easy transport. Spare parts and accessories are available, such as extra metal ballasts, sidewalls with doors and windows which can be produced upon customer request.



**Easy-Gazebo**  
with thermo-taping:  
even more resistant to water!



## FRAMES

### LIGHT STRUCTURE

LIGHT STRUCTURE / EASY TO HANDLE

Made with hexagonal aluminium profiles, 45 mm/0,8 mm thick.  
A strong and lightweight gazebo, easy to transport, it is delivered with pegs in a wheeled carry case on wheels



### PRO STRUCTURE

STRONG / DURABLE / SOLID

The best structure available on the market.  
Made with 40x40 mm/2,0 mm thick aluminium profiles, it is suitable for a professional and constant use, ideal for a frequent use. Built with stainless steel screws and extruded aluminium junctions. It is delivered with pegs in a wheeled carry case on wheels



## SIZE AND DIMENSIONS

2x2 m	3x3 m	3x4,5 m	4x4 m	6x3 m	8x4 m
Weight: 28 kg	Weight Pro: 36 kg Weight Light: 26 kg	Weight Pro: 46 kg Weight Light: 34 kg	Weight: 44 kg	Weight: 59 kg	Weight: 68 kg
Dimensions closed: 152x27x27	Dimensions closed: 152x27x27	Dimensions closed: 152x37x27	Dimensions closed: 202x27x27	Dimensions closed: 152x48x27	Dimensions closed: 202x50x27
Top height: 2,98 mt	Top height: 3,28 mt	Top height: 3,30 mt	Top height: 3,87 mt	Top height: 3,28 mt	Top height: 3,87 mt

## ACCESSORIES

### Kit 2 Flag holder Easy-Flag



Kit 2 Flag holder Easy-Flag to be fixed to the PRO Gazebo 40 mm frame

### Weight 15,5 kg for gazebo



Base plate for Pro and Light frames

### Kit 2 Couplers



Kit 2 x Couplers terminals for gazebo PRO frames (40mm)









### Gutter



Gutter for gazebos in a row.



**TECHNICAL SPECIFICATIONS OF THE STRUCTURES**

	STRUCTURE SECTION	FRAME	TUBE PROFILE	AVAILABLE SIZES	CONNECTION BARS	JOINT FIXING	SPRING TENSIONER	SCREWS	JOINTS	BASE FOOT
<b>LIGHT</b>	45MM / HEXAGONAL TELESCOPIC PILES THICKNESS 0.8 MM		Aluminum 45x40 HEX / 0,8 mm thickness	Square 3X3 Rectangular 3x4,5	25x12,5mm Aluminum	PRS / Pull Ring System	Spring ø 30mm	Stainless steel	Nylon	Steel
										
<b>PRO</b>	40MM / SQUARES TELESCOPIC POLES THICKNESS 2 MM		Aluminum reinforcement Section 40x40 / 2 mm thickness	Square 2x2 / 3x3 / 4x4 Rectangular 3x4.5 / 3x6 / 4x8	32x16mm Aluminum reinforcement	PRS / Pull Ring System	Spring ø 60mm	Stainless steel	Extruded Aluminum	Galvanized steel Aluminum
										

**TECHNICAL SPECIFICATIONS OF ROOF AND WALLS**

	FABRIC	CUSTOMIZATION
<b>NOT CUSTOMIZED</b>	Certified Fireproof Nylon - Tinto 200gr / m2	<div> <div></div> <div></div> </div> Black White
<b>CUSTOM</b>	Class 1 Fireproof Polyester - one-sided 250gr / m2	Colours and graphics are fully customizable – digital printed High resolution photographic images 150 dpi